



	REVISIONS								
REV	ECR	DATE	INITIAL	APPROVED					
1		released for production	7/13/2016	SM	JAG				
В	19-727	TEST LOAD SHEET ADDED	2019-05-16	VM	VM				





NOTES:

1. REF. EUROCOPTER T/N: 117 W3.


2. WEIGHT TEST TO A TOTAL 12,000 LBS. (6,000 LBS. PER SLING).


DART


					•						ROSPACE		
ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	TITLE	MAIN ROTORHEAD REMOVAL/INSTALLATION HOIST			
	Χ		-1	1	WELDMENT			2	DWG NO.	RRF117-W3			
	1		-3		FRAME	1018/1020 CR		3	MAT'L	.,,,,,	UNLESS OTHERWISE SPECIFIED		
	4		-5		HOOK	1018/1020 CR		4	HEAT TREAT		DIMENSIONS ARE IN INCHES  .XXX ± .005 FRACTIONS ± 1/8		
	4	B/O	-7		SPRING PIN	STEEL	Ø1/4 x 1-1/8 (MCMASTER-CARR # 98296A927)	2	FINISH		.XX ± .01 ANGLES ± .5° .XX ± .1 SURFACES = 125/		
		B/O	9	4	SPRING LATCH W/ BOLT & NUT	S.S.	1-5/8 x 9/16 x 3/8 (MCMASTER-CARR # 3526T72)	1	SPEC	1. BREAK ALL SHARP EDGES			
		B/O	-11	2	BASKET SLING		2 PLY, 2 IN x 36 IN, 12,800 LB CAPACITY (MSC # 85810844)	1	DRAWN BY:	CLOUGH	.015 x 45° OR .015R — 2. DIMENSIONAL LIMITS APPLY		
		B/O	-13	1	LANYARD CABLE		Ø1/16 x 8in (MCMASTER-CARR #30345T532)	1	OPPS APPR:		AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009		
		B/O	-15	1	SPLIT RING		1-1/16 OD X 15/16 ID X 1/8 THK (MCMASTER#90905A673)	1	QA APPR:	1./.()	USED ON MODEL		
		B/O	-17	1	METAL SCREW NAIL	STEEL	#10 (MCMASTER-CARR # 90081A240)	1	APPROVED:		EC145		
		B/O		1	DART PLACARD	ALUMINUM	RB41011	1	SCALE	1:6 PATE 20	010-08-05 SHEET 1 OF 5		

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			







TITLE MAIN ROTORHEAD REMOVAL/INSTALLATION HOIST

DWG NO.	RBE117-W3-1	

l .			•					
DWG NO.		RBE	11	7-W3-1	B			
MAT'L			UNLESS OTHERWISE SPECIFIED					
HEAT TREAT				DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8				
	DER COAT Y	ELLOW		.XX ± .03 ANGLES ±1° .X ± .1 SURFACES = 125/ 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY				
SPEC FED #	<del>1</del> 13538							
DRAWN BY:	CLOUGH	1						
CHECKED:	DUERFE	LDT		AFTER PLA	ATING			
OPPS APPR:	ANDERS	SON		3. INTERPRE ASME Y14.	T DIM AND TOL PER .5M-2009			
QA APPR:	LINDSAY	7			USED ON MODEL			
APPROVED:	GILBER1	Γ			EC145			
SCALE	1:4	DATE	201	0-08-05	SHEET 2 OF	5		

(-1)

WELDMENT

